





天长市永安消防装备有限公司

YONGAN FIRE SAFETY GROUP CO., LTD

ADD: NO 8, TIANCHA ROAD, CHANGJIANGTOWN, TIAN CHANG CITY ANHUI PROVINCE, CHINA. Website: <https://www.yongansafety.com/> \. Contact: Sophia Qu (general manager) Email: xiny0207@gmail.com Phone/WhatsApp: 008618225803110

Specification

Length × Width × Height	2965x1645x1945mm
Wheelbase	2060mm
Minimum Ground Clearance	330mm
Minimum Turning Diameter	8500mm
Curb Weight	911kg
Maximum Payload	749kg
Fuel Tank Capacity	45L
Passenger Capacity	3
Maximum Power / Corresponding RPM	90hp / 7250rpm
Maximum Torque / Corresponding RPM	94.5 N·m / 6500rpm
Power Mode	Three-cylinder, water-cooled, four-stroke, DOHC
Displacement	998cc
Drive Mode	4WD electronically controlled switch
Suspension Type	Front: High ground clearance independent double A-arm Rear: Independent double A-arm
Suspension Travel	Front: 280mm travel Rear: 260mm travel
Braking Method	Front: Dual disc brakes Rear: Single disc brake
Tire Specifications	Front tires: 29x9-14 Rear tires: 29x11-14
Maximum Towing Weight	1134 kg
Instrument Panel	8-inch MMI touchscreen display
Roof-mounted Speaker	Equipped
Lighting	Full-vehicle LED lighting
Windshield	Yes, with electric wipers and washer system
Rear Window	Yes, sliding
HVAC System	heating, ventilation, and air conditioning
Doors	Equipped with electric windows
Steering Wheel	41° adjustable
Seats	Front and rear seats adjustable by 150 mm
Fire truck body and fire pump system	
Brand Model	YONGAN25BQ High-pressure water mist fire pump with DC/straight stream spray mode switching
Rated flow rate of water spray	25L/min
Rated pressure of water spray	120Bar
Starting method	Electrical start



天长市永安消防装备有限公司

YONGAN FIRE SAFETY GROUP CO., LTD

ADD: NO 8, TIANCHA ROAD, CHANGJIANGTOWN, TIAN CHANG CITY ANHUI PROVINCE, CHINA. Website: <https://www.yongansafety.com/> \. Contact: Sophia Qu (general manager) Email: xiny0207@gmail.com Phone/WhatsApp: 008618225803110

Hose reel	60m length (which automatically retracts after use), equipping with high prssure fire gun/monitoir
Reaching distance	16m
Tank capacity	Water 220L, foam 30L
Others	Some other fire equipment can be customized mounted on the condition the space allows.